

The Following Dish Machines Require SMART FABRICATION™ Modifications For Dishtable Compatibility.

ADS (American Dish Machine)	ADC44, ADC66	Sink bowl must be 20" from dish machine. Add DTA-76 to soil dishtable.
	HT-25, SS-25	If dish machine is in corner, backsplash must be notched to 4" tall to clear handle. Add DTA-78 to table that's on front of machine.
Blakeslee	D-8, D-9	If dish machine is in corner, right side backsplash must be notched to 4" tall to clear handle. Add DTA-78 to the right table.
	RL40, RM50	Must maintain 13" clear on clean side of machine.
Champion	44KB, 54KB, 64KB	A special dish machine opening is required. Add DTA-77 to each dishtable.
CMA (Chemical Methods)	180	Right side sinks bowls must be 12" from dish machine. Add DTA-76 if sink is on right table.
Energymizer	44H, 44L, 66H, 66L	Sink bowl must be 12" from dish machine. Add DTA-76 to soil dish table.
Ecolab	ES-4400, ES-6600	Sink bowls on left side of machine must be 12" from dish machine. Add DTA-76 to soil table if required.
	ET-14	If sink is on right side of dish machine and deeper than 10", sink must be 16" from machine. Add DTA-76 to soil table if required.
	ET-44	A special dish machine opening is required. Add DTA-77 to each dish table. Right side sinks bowls must be 12" from dish machine. Add DTA-76 if sink is on right table.
Hobart	AM-12	Right side sink bowls must be 12" from machine. Add DTA-76 if sink is on right side. - MACHINE DISCONTINUED.
	AM-14	if sink is on right side of dish machine and is deeper than 10", sink must be 16" from dish machine. Add DTA-76 to soil table if required. - MACHINE IS DISCONTINUED.
	AM-15	If dish machine is in corner, left side backsplash return must be notched to 4" tall to clear handle, add DTA-78 . If soil table is on the left and dish machine is in corner, prerinse sink must move to 12" from dishmachine. Add DTA-76 .
	C-44, C-54, C-64, CRS-66, 38DDU, SL-23, SL-30	A special dish machine opening is required. Add DTA-77 to each dish table.
Intedge	DW-50	A special dish machine opening is required. Add DTA-77 to each dish table.
Insinger	Admiral 44	Must maintain 13" clear on clean side of machine. A special dish machine opening is required. Add DTA-77 to each dishtable.
	40-2	Start with BSR series table. Add K-508 to cut hole and install mounting flange. Add sink from page 78 if required. If additional length required use DTA-56 .
Jackson	TempstarTempstar HH	Right side sinks bowls must be 12" from dish machine. Add DTA-76 if sink is on right table.
	Tempstar GPX	No changes. Verify where 27.5" wide booster heater will fit on floor under table.
	100, 150	Sink bowls on left side of machine must be 12" from dish machine. Add DTA-76 to soil table if required. MACHINES ARE DISCONTINUED.
	AJ-44, AJ-54, AJ-64, AJ-66, AJ-76, AJ-80, AJ-86, AJ-90, AJ-100	Sink bowls on left side of machine must be 12" from dish machine. Add DTA-76 to soil table if required.
	Jackson 10 (round)	Start with BSR series table. Add 2 K-508 to cut hole and install mounting flange. Add sink from page 78 if required. If additional length required use DTA-56 .
Jet Tech	747, F-22	Dish machine newer than 1/2001 no modification required. Older machines add K-508 to each dish table to notch front and rear back 1" and lower backsplash to 6" tall. F-22 dish machines made prior to 9/2002 right side sink bowl must be 14" from dish machine. Add DTA-76 to soil table if required.
	F-22T	Right side sink bowls must be 14" from dish machine. Add DTA-76 if sink is on right table.
Meiko	DV80.2	If dish machine is in corner, backsplash on left side must be notched to 2" tall to clear handle. Add DTA-78 to left dishtable.
	K-44, K-54, K-64, K-66, K-76 K-80, K-86, K-90, K-100	Sink bowl must be 12" from dish machine. Add DTA-76 to soil dishtable.
Moyer Diebel	MH-60, MH-65	If dish machine is in corner, backsplash must be notched to 4" tall to clear handle. Add DTA-78 to left table. Add a second DTA-78 for left table to cut down front roll edge to 2".
Stero	SDRA, SD-2RA	If dish machine is in corner, manufacturer recommends a rear enclosure panel on the dishtable. Not available from Advance Tabco. However, standard dishtables will fit the dish machine. Right side sink bowls must be 12" from dish machine. Add DTA-76 if sink is on right table.
	SCT-44-CSA, SCT-66	A special dish machine opening is required. Add DTA-77 to each dish table. Right side sinks bowls must be 12" from dish machine. Add DTA-76 if sink is on right table.
Vulcan-Hart	3D20TF, 3D2FCD	Right side sink bowls must be 16" from dish machine. Add DTA-76 if sink is on right side.